



**PERPENDICULAR CURB RAMPS (TYPE 1)**

**RAMP TEXTURE DETAIL**

**TYPICAL SECTION THROUGH RAMP**

**PERPENDICULAR CURB RAMPS (TYPE 2)**

**NOTES:**

1. NO ABOVE GROUND UTILITIES ARE PERMITTED WITHIN RAMP AREA.
2. LANDINGS SHALL BE PLACED AT THE TOP OF EACH RAMP. LANDING SLOPES SHALL NOT EXCEED 50:1 IN ANY DIRECTION. MINIMUM LANDING DIMENSIONS SHALL BE 4' X 4'. THE SLOPE OF THE SURFACING AT THE BOTTOM OF THE RAMP SHALL NOT EXCEED 20:1 FOR A DISTANCE OF 2' (SEE TYPICAL SECTION ABOVE).
3. RAMP SURFACE SHALL BE TEXTURED WITH TRUNCATED DOME SURFACE PER DETAIL. MANUFACTURED 2' X 4' PANELS SHALL BE USED FOR NEW CONSTRUCTION. SURFACE APPLIED PANELS MAY BE USED ON EXISTING RAMPS.
4. APPROVED TRUNCATED DOME SURFACING MATERIALS:  
ARMORTILE (CAST IN PLACE AND SURFACE MATS)  
 AVAILABLE AT : WHITE CAP CONST. SUPPLY  
 503-287-4151  
CASTinTACT (CAST IN PLACE)  
 AVAILABLE AT : MASON'S SUPPLY CO.  
 503-234-4321

<b>CITY OF SANDY</b>	
<b>SIDEWALK ACCESS RAMPS</b>	
DATE: MARCH 2004	DRAWING NO. <b>206</b>