

GENERAL NOTES:

1. CONTRACTOR/OWNER TO VERIFY AND CONFIRM ALL CONDITIONS AND DIMENSIONS AND NOTIFY WEB STEEL BUILDINGS NORTHWEST, LLC (WSBNW) REGARDING DISCREPANCIES PRIOR TO START OF WORK.
2. DRAWING SCALES INDICATED ON PLANS ARE APPROXIMATE AND INTENDED TO BE USED FOR REFERENCE ONLY. DO NOT SCALE DRAWINGS FOR CONSTRUCTION PURPOSES.
3. GOVERNING BUILDING CODE: 2019 OREGON STRUCTURAL SPECIALTY CODE.
4. THE SUPPLYING OF STAMPED ENGINEERING CALCULATIONS AND DRAWINGS FOR THIS METAL BUILDING SYSTEM DOES NOT IMPLY OR CONSTITUTE AN AGREEMENT THAT WSBNW IS ACTING AS THE ENGINEER OR ARCHITECT OF RECORD OR DESIGN PROFESSIONAL FOR THE WHOLE OF THE PROJECT.
5. THESE DOCUMENTS ARE STAMPED ONLY AS TO THE COMPONENTS FURNISHED BY WSBNW. IT IS THE RESPONSIBILITY OF THE PURCHASER TO COORDINATE DRAWINGS PROVIDED BY WSBNW WITH OVERALL PROJECT AND/OR OTHER PLANS AND/ OR OTHER COMPONENTS, IN CASES OF DISCREPANCIES, DRAWINGS PROVIDED BY WSBNW SHALL GOVERN.
6. ANY FIELD MODIFICATIONS OR ALTERATIONS, OR THE ATTACHMENT OF ANY EQUIPMENT OR COMPONENT TO WSBNW METAL BUILDING OR THE OMISSION OF ANY PARTS OR PIECES SPECIFIED ON STAMPED DRAWINGS PROVIDED BY WSBNW WITHOUT THE EXPRESSED WRITTEN APPROVAL OF WSBNW SHALL VOID ANY AND ALL WARRANTIES AND RELEASE WSBNW FROM ANY AND ALL PROFESSIONAL LIABILITY AND/OR OBLIGATIONS.
7. PERIODIC SPECIAL INSPECTIONS, PER IBC CHAPTER 1705.2, ARE REQUIRED AT OWNER'S EXPENSE AND FOR THE FOLLOWING:
 - A) SINGLE PAGES FILLET WELDS NOT EXCEEDING 5/16"
 - B) A325 BOLT INSTALLATION USING TURN OF NUT WITH MATCH MARKING OR DIRECT TENSION INDICATOR METHODS OF INSTALLATION.
8. ANY ADDITIONAL INSPECTIONS REQUIRED BY BUILDING DEPARTMENT SHALL BE AT OWNER'S EXPENSE.
9. ALL WELDING SHALL BE PERFORMED AT WSBNW FABRICATION FACILITY IN SANDY, OREGON WITH ETO-XX ELECTRODES BY CERTIFIED WELDERS, NO FIELD WELDING REQUIRED.
10. STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING STANDARDS:
 - A) WIDE FLANGE SHAPES: ASTM A-992
 - B) CHANNEL SHAPES: ASTM A-36
 - C) ANGLE SHAPES: ASTM A-36 (42 KSI MIN. YIELD STRENGTH)
 - D) HSS TUBE SHAPES: ASTM-B500
11. SHOP PRIMER IS A RUST INHIBITIVE PRIMER. THE PAINT IS NOT INTENDED FOR LONG-TERM EXPOSURE TO THE ELEMENTS.
12. BOLTS SHALL CONFORM TO THE FOLLOWING STANDARDS:
 - A) ANCHOR BOLTS: ASTM A-307
 - B) BUILDING FRAME BOLTS: ASTM A-325, UNO.
 - C) ALL BOLT HOLES TO BE 1/16" LARGER THAN NOMINAL BOLT DIAMETER, UNO. INSTALL HARDENED WASHERS WHEREVER HOLE SIZE EXCEEDS THE BOLT DIAMETER PLUS 1/16". SIZE WASHER TO EXTEND BEYOND EDGES OF NUT OF BOLT HEAD.
13. REINFORCING STEEL SHALL CONFORM TO ASTM A-615, GRADE 60 FOR #4 BARS AND LARGER, GRADE 40 FOR #3 BARS. WELDED WIRE MESH SHALL CONFORM TO ASTM A-185 (TO KSI MIN. Fy). LAP 9LAP EDGE BARS MIDWAY BETWEEN COLUMNS. ALL LAPS TO BE 40 BAR DIAMETERS MIN, UNO.
14. CONCRETE STRENGTH: 3000 psi MIN. AT 28 DAYS (FOUNDATION DESIGN IS BASED UPON 2500 PSI)
15. GRADE BEAMS, PIERS, AND SPREAD FOOTINGS SHALL BE POURED ONTO UNDISTURBED, NATIVE SOIL WHICH IS FREE FROM ANY MATERIAL THAT WILL ADVERSELY AFFECT THE SOIL DESIGN BEARING PRESSURE REFERENCED ON THIS SHEET.
16. LUMBER SHALL BE DOUGLAS FIR-LARCH OF GRADE AND SIZE AS SPECIFIED IN ABOVE NOTES AND ON PLANS. ALL NAILS USED SHALL BE 'COMMON' TYPE, UNO. FACE NAIL ALL MULTIPLE 2x MEMBERS TOGETHER WITH 16d NAILS @ 24" o/c, UNO.
17. LAG SCREW LOAD VALUES CONFORM TO NDS. TABLES 11K AND 10.3.2 PRE DRILL HOLES, IF NECESSARY, TO PREVENT SPLITTING OF WOOD.
18. SILL PLATE SHALL BE 2x PRESSURE TREATED ATTACHED TO FOUNDATION WITH: 1/2" φ SILL PLATE BOLTS (PROVIDED BY OTHERS) AT 4' o/c WITH 1" MIN. EMBEDMENT. PROVIDE ONE FASTENER OR ANCHOR BOLT WITHIN 6" OF MEMBER ENDS. MAINTAIN 2" MIN. EDGE DISTANCE FOR ALL SILL PLATE FASTENERS. NOTE: SEE DOOR FRAMING DETAIL SHEETS (AND SHEAR WALL DETAIL SHEET, IF PROVIDED) FOR SILL PLATE ATTACHMENTS THAT ARE REQUIRED IN ADDITION TO BOTH OPTIONS INDICATED ABOVE.
19. SHEET METAL SIDING AND ROOFING, SHALL BE MIN. 29 GA. UNLESS NOTED OTHERWISE. FASTEN TO PURLINS & GIRTS WITH MINIMUM #9 SCREWS @ 9" o/c, OR AS RECOMMENDED BY MANUFACTURER. SEE MANUFACTURER'S LITERATURE FOR ALLOWABLE SPAN INFORMATION AND ATTACHMENT TO SUPPORTING MEMBERS (MANUFACTURER IS RESPONSIBLE FOR ENSURING THAT PANEL AND ATTACHMENT WILL SUPPORT THE LOADS LISTED). CUSTOMER ACCEPTS ALL RESPONSIBILITY AND LIABILITY FOR ANY SIDING OR ROOFING MATERIAL USED THAT IS NOT PROVIDED BY WSBNW.

CUSTOMER APPROVAL:

ALL INFORMATION CONTAINED HEREIN HAS BEEN REVIEWED AND FOUND TO BE CORRECT AND CONSISTENT WITH MY INTENT AND PURPOSE. I REQUEST THAT WEB STEEL BUILDINGS NW PROCEED WITH FABRICATION, INSTALLATION AND ACCEPT ALL CUSTOMER RESPONSIBILITIES.

REVISE AND RESUBMIT
 APPROVED FOR FABRICATION AS NOTED
 APPROVED FOR FABRICATION

SIGNED: _____ DATE: _____

DESIGN LOADS:

OCCUPANCY CATEGORY	II
ROOF SNOW LOAD (psf)	30
WIND LOAD (3 Sec. Gust)	130 mph / EXP 'B'
SOIL BEARING PRESSURE (psf)	1500
ROOF PURLINS DEFLECTION CRITERIA	L/240 (LIVE LOAD)
WALL GIRTS DEFLECTION CRITERIA	L/180 (TOTAL LOAD) L/120 (WIND LOAD)

ABBREVIATIONS:

- CL - CENTERLINE
- PL - PLATE
- WF - WIDE FLANGE
- Ø - DIAMETER
- A.B. - ANCHOR BOLT
- D.A. - DRILLED ANCHOR
- EXP. - EXPOSURE
- EXT. - EXTERIOR
- INT. - INTERIOR
- MAX. - MAXIMUM
- MIN. - MINIMUM
- o/c - ON CENTER
- P.T. - POINT
- REQ'D - REQUIRED
- SIM. - SIMILAR
- STYL. - SYMMETRICAL
- TYP. - TYPICAL
- UNO. - UNLESS NOTED OTHERWISE


DRAWING INDEX


N1	GENERAL NOTES
N2	FRAMING DETAILS
1	FOUNDATION PLAN
2	ROOF FRAMING PLAN
3	FRONT SIDEWALL DETAILS
4	REAR SIDEWALL DETAILS
5	LEFT ENDWALL DETAILS
6	RIGHT ENDWALL DETAILS
1	FRAME HALF
C1	ANCHOR BOLT DETAILS
C2	FOUNDATION DETAILS
S1	RAFTER CONNECTION DETAILS
S2	FABRICATION DETAILS
S3	X-BRACE DETAILS
S4	EAVE DETAILS
S5	EAVE FRAMING DETAILS
D1	DOOR FRAMING DETAIL

STORAGE BUILDING
 37625 SUNSET STREET
 SANDY, OR 97055




DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057







TYP. GIRT CLIP (GC28) DETAIL




CORNER GIRT CLIP (CC212) DETAIL




TYP. PURLIN CLIP (PC810) DETAIL



BRACE DETAIL: SINGLE & DOUBLE BRACES



GIRT-TO-FASCIA BOARD DETAIL



WALL GIRTS: #2 DOUGLAS FIR @ 24" o/c			
MARK	TYPE	QUANTITY	
G10	2x6x10	6	
G12	2x6x12	1	
G14	2x6x14	1	
G16	2x6x16	4	
G18	2x6x18	5	



DOOR FRAMING NOTES:

- CANTILEVER WALL GIRTS PAST FRAME LEGS TO OVERHEAD DOOR JAMBS.
- CONTINUOUS WALL GIRTS BETWEEN DOOR JAMBS
- FOR REMAINING FRAMING DETAIL 5 SEE SHEET D1.


(A) 2x6 BLOCKING EXTENDS TO ROOF FRAMING. ATTACH TO DOOR TRIMMER W/CS16 STRAP WITH 16" MIN. END LENGTH.

(B) ATTACH 1/2" PLYWOOD (OR OSB) TO WALL FRAMING & EDGE PURLIN WITH 8d NAILS AT 6" o.c. AT PANEL EDGES AND 12" o.c. AT INTERMEDIATE FRAMING. BLOCK ALL PANEL EDGES (NOT SHOWN).

NOTE:
 1. CUSTOMER TO PROVIDE 1/2" PLYWOOD AND BLOCKING.
 2. SHEET ENTIRE WALL w/ 1/2" PLYWOOD.




2 FRONT SIDEWALL SIDING ELEV. @ LINE A
 VIEW FROM OUTSIDE THE BUILDING @ LINE A
 1/8" = 1'-0"




WALL GIRTS: #2 DOUGLAS FIR @ 24" o/c			
MARK	TYPE	QUANTITY	
G10	2x6x10	--	
G12	2x6x12	--	
G14	2x6x14	5	
G16	2x6x16	5	

- DOOR FRAMING NOTES:**
1. CANTILEVER WALL GIRTS PAST FRAME LEGS TO OVERHEAD DOOR JAMBS.
 2. CONTINUOUS WALL GIRTS BETWEEN DOOR JAMBS
 3. FOR REMAINING FRAMING DETAILS SEE SHEET D1.



1 REAR SIDEWALL ELEVATION @ LINE D
 4 VIEW FROM OUTSIDE THE BUILDING @ LINE D
 1/8" = 1'-0"




2 REAR SIDEWALL SIDING ELEV. @ LINE D
 4 VIEW FROM OUTSIDE THE BUILDING @ LINE D
 1/8" = 1'-0"

WEB STEEL
 Buildings Northwest
 37396 RUBEN LANE
 SANDY, OR. 97055
 OFFICE: (503)-668-7211 FAX: (503)-668-9026


DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057

REAR SIDEWALL DETAILS
 ELEVATION & SIDING PLAN
 (AT LINE D)


RENEWAL: DEC. 31, 2019




WALL GIRTS: #2 DOUGLAS FIR @ 24" o/c			
MARK	TYPE	QUANTITY	
G10	2x6x10	--	
G12	2x6x12	--	
G14	2x6x14	--	
G16	2x6x16	--	



1 LEFT ENDWALL ELEVATION @ LINE 1
 5 VIEW FROM OUTSIDE THE BUILDING @ LINE 1
 1/8" = 1'-0"



2 LEFT ENDWALL SIDING ELEV. @ LINE 1
 5 VIEW FROM OUTSIDE THE BUILDING @ LINE 1
 1/8" = 1'-0"




WEB STEEL Buildings Northwest 37396 RUBEN LANE SANDY, OR. 97055 OFFICE: (503)-668-7211 FAX: (503)-668-9026	DRAWN: NSC
	DATE: 12/10/2019
	JOB NO: V19-057

LEFT ENDWALL DETAILS
 ELEVATION & SIDING PLAN
 (AT LINE 1)


NOTE:
COLUMN BRACE
(PER SHEET N2)
@ 10'-0" TYP.

SYM	DESCRIPTION	LENGTH	MEMBER	QTY
▼	RAFTER BRACE	18"	1x1x1/8"	2
●	COLUMN BRACE	18"	1x1x1/8"	2
ERA3	ENDWALL RAFTER A3		C8x11.5	
ERD3	ENDWALL RAFTER D3		C8x11.5	
ECA3	ENDWALL COLUMN A3		HSS3x3x3/16	
ECB3	ENDWALL COLUMN B3		W6x12	
ECC3	ENDWALL COLUMN C3		W6x12	
ECD3	ENDWALL COLUMN D3		HSS3x3x3/16	


WALL GIRTS: #2 DOUGLAS FIR @ 24" o/c	MARK	TYPE	QUANTITY
	G10	2x6x10	1
	G12	2x6x12	7
	G14	2x6x14	12
	G16	2x6x16	-




1 RIGHT ENDWALL ELEVATION @ LINE 3
VIEW FROM OUTSIDE THE BUILDING @ LINE 3
1/8" = 1'-0"
6




2 RIGHT ENDWALL SIDING ELEV. @ LINE 3
VIEW FROM OUTSIDE THE BUILDING @ LINE 3
1/8" = 1'-0"
6





1
7
CUSTOM FRAME HALF
NO SCALE

DARK TRIANGLES INDICATE DOUBLE "A" BRACE, HOLLOW TRIANGLES INDICATE SINGLE "A" BRACE, PER SHEET N2



MARK	DESCRIPTION	LENGTH	MEMBER	QTY
FB30	30" FRAME BRACE	30"	L1"x1"x1/8"	2
FB36	36" FRAME BRACE	36"	L1"x1"x1/8"	2
FB42	42" FRAME BRACE	42"	L1"x1"x1/8"	5

NOTES:

- UNEQUAL LEG ANGLES TO BE PLACED WITH LONG LEG IN THE PLANE OF THE FRAME.
 - FOR WELDING REQUIREMENTS, SEE SHEETS S2 & S3.
- | | |
|------------------------|-------------------|
| DEAD LOAD | 5 psf |
| ROOF SNOW LOAD | 30psf |
| WIND LOAD (3 sec GUST) | 130 mph, EXP. 'B' |
| FRAME TRIBUTARY WIDTH | 9'-0" |
| TOTAL FRAME WEIGHT | 1050 lbs. |


KEY	
UPPER CHORD	L3x3x.1875
LOWER CHORD	L3x3x.1875
INNER LEG	L3x3x.25
OUTER LEG	L3x3x.1875

A	L1x1x.125
B	L1.5x1.5x.125
C	L2x2x.125
D	L2x2x.1875
E	L2x2x.25
G	L2x2x.375
H	L3x2x.1875
J	L3x2x.25
L	L3x2x.375
M	L3x3x.1875
N	L3x3x.25
Q	L3x3x.375
R	L3x3x.5
S	L4x3x.25
U	L4x3x.375
V	L4x4x.25
X	L4x4x.375
Y	L4x4x.5
Z	L6x4x.375


WEB STEEL
Buildings Northwest
37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026

DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057


FRAME HALF
40'-0" WIDE x 11'-9 15/16" EAVE
3:12 PITCH




1 ENDWALL PEAK DETAIL
 S1 VIEWED FROM INSIDE THE BUILDING 1 1/2" x 1'-0"



3 ENDWALL RAFTER TO COLUMN DETAIL
 S1 VIEWED FROM INSIDE THE BUILDING 1 1/2" x 1'-0"




2 ENDWALL PEAK DETAIL @ COLUMN
 S1 VIEWED FROM INSIDE THE BUILDING 1 1/2" x 1'-0"



SHEET S1	RAFTER CONNECTION DETAILS	 WEB STEEL LLC Buildings Northwest 37396 RUBEN LANE SANDY, OR. 97055 OFFICE: (503)-668-7211 FAX: (503)-668-9026	DRAWN: NSC
			DATE: 12/10/2019
			JOB NO: V19-057

NOTE:
DURING INITIAL X-BRACE INSTALLATION, TIGHTEN CABLE SUCH THAT NO SAG OCCURS, THEN TURN NUT AT ONE END AN ADDITIONAL (2) FULL TURNS.


CUSTOMER SHALL PERFORM PERIODIC INSPECTION OF ALL X-BRACING CABLES TO ENSURE TIGHTNESS. IF CABLES HAVE LOOSENED, REPEAT INSTALLATION PROCEDURE ABOVE.




NOTE: ATTACH AT BASE OF COLUMN AND AT ROOF X-BRACING IN SIMILAR MANNER

NOTE: AT WALL X-BRACING, ORIENT DIRECTION OF 3" LEG (LEG WITH HOLE) TOWARD WALL GIRTS (AS SHOWN). DRILL 3/4" HOLES THROUGH WALL GIRT AND PASS CABLE THROUGH HOLES.


LOCATION	ASSEMBLY DESIGNATION			
	EYEBOLT	GRIP LENGTH	CABLE	CONN. ANGLE
ALL	FW 250 BA			
	1/2" ϕ	19 1/2" LONG	1/4" ϕ	L5X3X3/8 x 2 1/2"
	FW 375 BA			
-	FW 500 BA			
	5/8" ϕ	30" LONG	3/8" ϕ	L5X3X1/2 x 3"
-	1/8" ϕ	36" LONG	1/2" ϕ	L6X4X1/2 x 3 1/2"



FRAME JOINT AT 2-MEMBER CONN.



FRAME JOINT AT 3-MEMBER CONN.



STIFFENER WELDING

S3

NO SCALE

STIFFENER NOTES:

1. WELD LEG SIZE TO MATCH STIFFENER THICKNESS.
2. TOTAL WELD LENGTH AT THE ENDS IS THE SAME AS NOTE 3 OF WELDING REQUIREMENT, DET. 2/53.
3. AT INNER LEG STIFFENERS, EXTEND TO WITHIN 6" OF HAUNCH CONNECTION AT TOP ANGLE AND WITHIN 6" OF BASE PLATE AT BOTTOM.

WELDING REQUIREMENTS (DET. 2/53)

1. CENTERLINES OF WEB MEMBERS SHALL ALIGN AT COMMON POINT AS SHOWN.
2. FILLET WELD LEG SIZE TO MATCH WEB MEMBER THICKNESS, MIN. TOTAL WELD LENGTH AT EA. END OF MEMBER:
4" FOR L 1 x 1
5 1/2" FOR L 1.5 x 1.5
7" FOR L 2 x 2
10" FOR L 3 x 3
3. WELDING SEQUENCE: WELD 'A' FIRST, WELD 'B' SECOND, THEN WELD 'C'.
4. CLIP CORNER OF WEB MEMBER AS REQ'D TO ATTAIN SPECIFIED WELD. WELD ON BACK IF MIN. WELD NOT POSSIBLE ON FRONT.

FRAME WELD CONNECTION

S3

NO SCALE

X-BRACING CONN. DETAILS

S3

NO SCALE



RENEWAL: DEC. 31, 2022

WEB STEEL INC.
Buildings Northwest
37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026



DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057

X-BRACE DETAILS

SHEET S3

3
S4

CORNER PLAN VIEW



1
S4

EAVE AT ENDWALL

VIEWED FROM INSIDE THE BUILDING



1 1/2" = 1'-0"

NOTE: WORK THIS SHEET WITH PLAN VIEW - AT SIDEWALLS AND ENDWALLS ON SHEET S5.

2
S4

EAVE AT BUILDING FRAME

1 1/2" = 1'-0"




STANDARD EAVE DETAILS

WEB STEEL llc
Buildings Northwest
37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026

DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057


SHEET
S4





1
55

PLAN VIEW - STANDARD EAVES AT SIDEWALL AND ENDWALL




NO SCALE



SHEET 55	EAVE FRAMING DETAILS PLAN VIEW AT STANDARD EAVES AND STANDARD GABLES (NO EXTENSION)	 WEB STEEL <small>LLC</small> Buildings Northwest 37396 RUBEN LANE SANDY, OR. 97055 OFFICE: (503)-668-7211 FAX: (503)-668-9026	DRAWN: NSC
			DATE: 12/10/2019
			JOB NO: V19-057



- NOTES:
1. SHEATH ENTIRE WALL w/ 1/2" PLYWOOD (PROVIDED BY CUSTOMER)
 2. FRAME AND/OR COLUMNS NOT SHOWN FOR CLARITY




ANCHOR BOLT DETAILS



37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026

DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057

REINFORCING BARS (SEE SCHEDULE BELOW FOR SIZE AND NUMBER OF BARS WHICH MAY DIFFER FROM THOSE SHOWN). PLACE AT LEAST ONE TOP BAR TO OUTSIDE OF ANCHOR BOLTS AT FRAME AND COLUMN BASES. EXTEND BARS 24" MIN. AROUND CORNERS.)



LOCATION:	WIDTH	DEPTH	TOP BARS	BOTTOM BARS
1A/C2	18"	18"	(2)-#4	(2)-#4
1B/C2	18"	18"	(2)-#4	(2)-#4



6x6 - W1.4 x W1.4 WELDED WIRE MESH @ SLAB CENTER (LAP SPLICE 6" MIN.) SEE NOTE FOR ALTERNATE #6.

4" CONCRETE SLAB

THICKENED SLAB CENTERED AT EACH BUILDING FRAME

NOTE: SLAB DESIGN PROVIDED IS BASED ON A MAX. 2000# CONCENTRATED LOAD SUPPORTED BY SOIL WITH A MIN. ALLOWABLE BEARING PRESSURE (ABP) AS SHOWN ON SHEET N1. SLAB DESIGN FOR LOADS EXCEEDING ABOVE LOAD OR WITH SOIL WITH LESS ABP SHALL BE PROVIDED BY OTHERS.


1 TYPICAL SLAB EDGE DETAIL
C2
1 1/2" = 1'-0"



THICKEN SLAB TO 8" DEEP BY 12" WIDE AT CENTER OF FRAMES w/ (1) #4 SIDEWALL TO SIDEWALL WITH STANDARD HOOK AND 3" CLEAR OF BOTTOM

NOTES:


1. FOUNDATION AND SLAB DESIGN IS BASED UPON 1500 PSF ALLOWABLE FOUNDATION PRESSURE.
2. MATERIAL SUPPORTING FOUNDATION SHALL BE A DRY GRANULAR WELL DRAINING MATERIAL.
3. GROUND LOCATIONS THAT DO NOT MEET MINIMUM DESIGN REQUIREMENTS SHALL BE REMOVED AND REPLACED WITH COMPACTED MATERIAL DESIGNED BY OTHERS, TO PROVIDE A UNIFORM SUBGRADE.
4. FOUNDATION DRAINAGE, DAMP PROOFING, AND CONCRETE FINISH ARE BY OTHERS.
5. CONTRACTOR TO PROVIDE SAW CUT JOINTS, AS RECOMMENDED BY LOCAL INDUSTRY ACI OR PCA STANDARDS, FOR SURFACE CRACK CONTROL. ENSURE SPECIFIED REINFORCING RUNS CONTINUOUSLY THROUGH ALL JOINTS. FILL JOINTS WITH SEMI-RIGID FILLER.
6. FIBROUS REINFORCING WITH A CURRENT ICC EVALUATION REPORT, MAY BE USED FOR SURFACE CRACK CONTROL. MANUFACTURER'S SPECIFICATIONS SHALL BE FOLLOWED.
7. THE BARS, IF SPECIFIED, SHALL RUN CONTINUOUSLY THE FULL WIDTH OF THE STRUCTURE AND TERMINATE AT EACH SIDEWALL FOUNDATION WITH A STANDARD HOOK AND 3" OF COVER.
8. SEE SHEET N1 GENERAL NOTES FOR ADDITIONAL INFORMATION.




FOUNDATION DETAILS

WEB STEEL
Buildings Northwest
37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026


DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057




1 ENTRY DOOR FRAMING DETAIL
D1
NO SCALE




2 OHD FRAMING DETAIL
D1
NO SCALE



3 JAMB DETAIL
D1
NO SCALE




3 OHD SPRING BOX
D1
1 1/2" = 1'-0"



4 OHD JAMB SECTION
D1
NO SCALE


HEADER & JAMB CONNECTION SCHEDULE
 (2) 2x6- (2) ROWS 16d NAILS AT 8" oc
 (3) 2x6- (2) ROWS 16d NAILS AT 8" oc ON EACH FACE
 (4) 2x6- 9D525600 SCREWS AT 8" oc (STAGGERED)
 -1/4" MAY BE REMOVED FROM THE 2X FACE AT ANGLE LOCATIONS



DRAWN:	NSC
DATE:	12/10/2019
JOB NO.:	V19-057

WEB STEEL LLC
 Buildings Northwest
 37396 RUBEN LANE
 SANDY, OR. 97055
 OFFICE: (503)-668-7211 FAX: (503)-668-9026

DOOR FRAMING DETAILS
 (SIDEWALL & ENDWALL DOORS)




1 FOUNDATION PLAN
1/8" = 1'-0"


PRESSURE TREATED SILL PLATE		
MARK	TYPE	QUANTITY
PT10	2x6x10	1
PT12	2x6x12	1
PT14	2x6x14	4
PT16	2x6x16	1

DRAWN:	NSC
DATE:	12/10/2019
JOB NO:	V19-057


WEB STEEL
Buildings Northwest
37396 RUBEN LANE
SANDY, OR. 97055
OFFICE: (503)-668-7211 FAX: (503)-668-9026

FOUNDATION PLAN






1
 S2
 FRAME EAVE
 1 1/2" = 1'-0"




2
 S2
 FRAME PEAK DETAIL
 1 1/2" = 1'-0"




TYP. CHORD SPLICE
 1 1/2" = 1'-0"

- NOTES:
1. SEE SHEET S3 FOR MEMBER WELDING NOT SHOWN.
 2. USE 3/4"φ BOLTS AT LOCATIONS SHOWN. CENTER OF BOLTS TO BE 1 1/2" FROM OUTSIDE EDGE OF PERPENDICULAR LEG OF ANGLE.
 3. IF SPECIFIED WELD LENGTHS ARE NOT ALL POSSIBLE ON FRONT SIDE SHOWN, PLACE REMAINDER ON BACK SIDE.



SHEET S2	FABRICATION DETAILS 2'-0" TRUSS	WEB STEEL Buildings Northwest 37396 RUBEN LANE SANDY, OR. 97055 OFFICE: (503)-668-7211 FAX: (503)-668-9026	DRAWN: NSC
			DATE: 12/10/2019
			JOB NO: V19-057



1 ROOF FRAMING PLAN
1/8" = 1'-0"

PURLINS: #2 DOUGLAS FIR @ 24" o/c		
MARK	TYPE	QUANTITY
P10	2x10x10	--
P12	2x10x12	--
P14	2x10x14	22
P16	2x10x16	22

FASCIA: #2 DOUGLAS FIR		
MARK	TYPE	QUANTITY
F10	2x10x10	4
F12	2x10x12	4
F14	2x10x14	--
F16	2x10x16	--

RIDGE CAP
(QTY: 3)

TYPICAL BOTH
ENDWALLS

